

ALUMINIUM HT CABLE (A-SERIES)



The A-series aluminium high voltage electric fencing insulated cable is used as a lead out cable from your energizer to the fence and for all other insulated high voltage transmissions. It is used with a range of aluminium wires and galvanised earth spikes. Available in single core or three core options.

Features:

- Ideal cable when aluminium wire is used
- Low electrical resistance reducing power and voltage drops over large distances
- The 3 core A-Series reduces installation time
- 30m 3 core cables are suitable for Wizord 2, Wizord 4, Merlin 4i, Druid 13LCD, Druid 15LCD, Druid 18LCD, Druid 25LCD and Druid 28LCD energizers
- 100m 3 core cables are suitable for Wizord 2, Wizord 4, Merlin 4i, Druid 13LCD, Druid 15LCD and Druid 18LCD energizers
- Max distance of 3 core cables suitable for Merlin M18S and Merlin M28S is 15m

Specifications:

Material	Aluminium UV stabilised double insulated cable
Roll size	30m 100m 200m 500m 1000m
Type	3 Core Stranded Core Solid Single Core
Colour	Black
Conductors	3 core HT cable - 1.6mm stranded inner conductors Single core HT cable - 1.6mm solid inner conductor

Stock Code	Description
EH-3AS030	3 core Aluminium HT Cable (A-series) 30m
EH-3AS100	3 core Aluminium HT Cable (A-series) 100m
EH-AS100	Solid Aluminium HT Cable (A-series) 100m
EH-AS200	Solid Aluminium HT Cable (A-series) 200m
EH-AS500	Solid Aluminium HT Cable (A-series) 500m
EH-AS1000	Solid Aluminium HT Cable (A-series) 1000m